



DISCOVER THE **PREMIER GEM** OF HEATING AND COOLING



- HIGH EFFICIENCY,
38 SEER / 15 HSPF
- G10 INVERTER
TECHNOLOGY
- INTELLIGENT
DEFROST
- SELF-DIAGNOSIS
- SIMPLE OPERATION

THE HALLMARK OF ELEGANCE & FUNCTIONALITY.

With the Sapphire wall mount ductless mini-splits, you can keep any room comfortable without sacrificing aesthetics. The quiet, unobtrusive design delivers advanced performance with an industry-best energy efficiency rating of up to 38 SEER in cooling and 15 HSPF in heating.

- WiFi included
- Ultra heat down to -22°F
- Energy Star®
- High efficiency, up to 38 SEER / 15 HSPF
- Precise airflow control
- Multiple fan speeds
- Intelligent preheating
- Intelligent defrost
- Low voltage start-up
- Sleek look to blend with your decor
- I-Feel function
- Privacy lock mode
- Sleep function
- Timer function
- Self-diagnosis
- Advanced filter options



MODEL		SAP09HP230V1A	SAP12HP230V1A	SAP18HP230V1A	SAP24HP230V1A
System Type		HEAT PUMP			
SYSTEM PERFORMANCE					
Cooling Capacity (Min-Max)	Btu/h	9000 (1535 - 12966)	12000 (2900 - 15354)	18000 (4094 - 21837)	22000 (6800 - 30700)
Heating Capacity (Min-Max)	Btu/h	9000 (2388 - 13648)	12200 (3071 - 18766)	18000 (4094 - 24566)	24000 (6800 - 32000)
SEER / EER		38 / 16.67	30.5 / 15.3	24.5 / 13.54	21.5 / 13
HSPF / COP		15 / 4.47	14 / 3.8	12 / 3.52	12 / 3.5
Energy Star®		YES			
Cooling Temperature Range	°F	0 - 129	0 - 129	0 - 129	0 - 129
Heating Temperature Range	°F	-22 - 75	-22 - 75	-22 - 75	-22 - 75
INDOOR UNIT					
		SAP09HP230V1AH	SAP12HP230V1AH	SAP18HP230V1AH	SAP24HP230V1AH
Air flow (Min-Max)	CFM	206 - 424	235 - 500	353 - 736	383 - 824
Sound Pressure Level (Cooling / Heating)	dB(A)	19 - 46 / 19 - 46	22 - 49 / 22 - 49	34 - 51 / 34 - 51	27 - 54 / 37 - 55
Dehumidification	pt/hr	1.69	2.96	3.8	4.23
Condensate Drain Size (OD)	in	5/8	5/8	5/8	5/8
Unit Dimension (WxHxD)	in	39 7/8 x 12 1/8 x 8 3/4	39 7/8 x 12 1/8 x 8 3/4	44 3/16 x 13 x 9 13/16	44 3/16 x 13 x 9 13/16
Package Dimension (WxHxD)	in	42 7/16 x x 14 13/16 x 11 13/16	42 7/16 x x 14 13/16 x 11 13/16	46 7/8 x x 16 x 13 3/16	46 7/8 x x 16 x 13 3/16
Weight (Net / Gross)	lbs	29.8 / 36.4	29.8 / 36.4	36.4 / 44.1	35.3 / 41.9
OUTDOOR UNIT					
		SAP09HP230V1AO	SAP12HP230V1AO	SAP18HP230V1AO	SAP24HP230V1AO
Compressor Type		GREE G-10 / 2 - STAGE INVERTER			
Sound Pressure Level (Cooling / Heating)	dB(A)	57 / 57	53 / 53	59 / 59	59 / 59
Unit Dimension (WxHxD)	in	35 13/32 x 23 1/2 x 14 7/8	35 13/32 x 23 1/2 x 14 7/8	38 5/8 x 31 1/8 x 16 13/16	38 5/8 x 31 1/8 x 16 13/16
Package Dimension (WxHxD)	in	37 3/16 x 24 13/16 x 16 7/16	37 3/16 x 24 13/16 x 16 7/16	42 1/2 x 33 1/8 x 19 1/8	42 1/2 x 33 1/8 x 19 1/8
Weight (Net / Gross)	lbs	99.2 / 105.8	105.8 / 49.4	141.1 / 152.1	147.7 / 158.8
Refrigerant Charge - R410A	oz	50.4	49.4	70.6	81.1
Coil Type		Aluminum Fin-Copper Tube / Acrylic Resin Protection			
REFRIGERANT PIPING					
Line Set Size (Liquid - Gas)	in	1/4 - 1/2	1/4 - 1/2	1/4 - 5/8	1/4 - 5/8
Pre-Charge Length	ft	25			
Pipe Length (Min / Max)	ft	10 / 49	10 / 98	10 / 131	10 / 164
Max. Pipe Elevation	ft	33	49	66	98
ELECTRICAL					
Power Supply		208-230V / 1Ph / 60Hz			
Rated Current Cooling	amps	6.2	6.5	10.8	16.4
Rated Current Heating	amps	6.9	6.9	10.8	16.4
MCA	amps	9	9	22	22
MOCP	amps	15	15	30	35
Main Power Wire Size	AWG	Per Local Code			
Interconnecting Wire Size	AWG	14 / 4			
LIMITED WARRANTY		5 Years Parts and Compressor - Residential			